

HEARING PROTECTION CLASSIC EARMUFFS

PRODUCT DATA SHEET: EMCLA

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
EMCLA



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 27dB.
- Hearing protection for noise levels to 110dB(A).
- Lightweight, comfortable and economical.
- High Level 27dB SLC₈₀ hearing protection.
- Adjustable headband for easy fit and greater comfort.
- Headband equalizes pressure and ensures cushions stay in position.
- Minimal pressure on the top of the head with its comfort headband.
- Soft, wide cushions fit comfortably around the ears.

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use.

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



ADJUSTABLE



COMFORT



REUSABLE



LIGHTWEIGHT

PRODUCT DETAILS

Weight:	151g
Clamping Force:	11.6N
Colour:	Black
Size:	Adjustable

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
EMCLA	BLACK	EACH	1	25

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	16.6	14.5	23.4	34.0	34.8	39.2	38.0
Standard Deviation	3.1	2.1	3.8	3.1	1.9	3.5	3.4
Mean-Minus-Standard Deviation Attenuations	13.5	12.4	19.6	30.9	32.9	35.7	34.6

SLC₈₀ Value is 27dB (Class 5)

STANDARDS

CERTIFIED TO:

AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC₈₀ 27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMK 40540

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR

FROM

PARAMOUNT
SAFETY PRODUCTS