

# HEARING PROTECTION MAMBA SLIMLINE PRO SERIES FOLDING EARMUFF

PRODUCT DATA SHEET: EMAMMF

**PRO**  
PRO CHOICE SAFETY GEAR

PRODUCT CODE:  
EMAMMF



## FEATURES AND BENEFITS

- Class 5 SLC<sub>90</sub> 28dB Attenuation.
- Hearing protection for noise levels to 110dB(A).
- Dielectric earmuff and headband - manufactured with non-conductive material.
- Fully adjustable telescopic arms with folding action for easy/compact storage.
- Contemporary low-profile design.
- High density sound reducing cup wall.
- High quality acoustic insulation foam.
- Premium soft touch ear cushions.
- Balanced clamping force for long duration wearer comfort.

## PRODUCT DETAILS

Clamp Force:	10.4N
Materials of construction:	
- Headband:	UPE/POM/PU Foam
- Cup:	ABS
- Insert:	PU FOAM
- Cushion:	PU
Weight:	268 grams
Size:	Standard One Size

## APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



ADJUSTABLE



COMFORT



HYGIENIC



REUSABLE



DIELECTRIC

## CARE INSTRUCTIONS

- Store in a cool, dry place.
- Avoid excessive UV exposure.
- Clean with mild detergent and water, allow to dry before use.
- Inspect headband and cup seals for wear and tear before use.

## AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
EMMAMF	BLACK/GREEN	EACH	1	20

## TEST DATA

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	17.1	19.7	27.5	33.1	34.2	36.5	35.1
Standard Deviation	5.5	4.1	5.3	4.7	4.0	3.7	5.5
Mean-Minus-Standard Deviation Attenuations	11.6	15.6	22.2	28.4	30.2	32.8	29.6

## STANDARDS

### CERTIFIED TO:

AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC<sub>90</sub> 28dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.



AS/NZS 2161.3  
Lic BMP754963

### PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,  
GNANGARA, WA 6077  
TECH SUPPORT: 1300 275 820  
CUSTOMER SERVICE: 1300 770 723  
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

### PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,  
EAST TAMAKI, AUCKLAND 2013  
TECH SUPPORT: 0800 888 778  
CUSTOMER SERVICE: 0800 888 778  
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM  
PARAMOUNTSAFETY.COM



FROM

PARAMOUNT  
SAFETY PRODUCTS