

ARAX GOLD PU DIP GLOVE

PRODUCT CODE: AFYPU(SIZE)



FEATURES & BENEFITS

- EN388:2016 Cut Resistance Level "D".
- ASTM Cut Level 4.
- Hi-vis polyurethane (PU) coated palm with anti-static liner.
- Excellent dexterity - Bare Hand Technology (BHT).
- Lightweight & Breathable Arax® liner.
- Form fitting for comfortable all day wear.
- Colour coded cuff for size identification.

APPLICATIONS

Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling

PRODUCT DETAILS

- Material** : 15 Gauge Seamless Arax® Liner
Dip : Hi-vis Polyurethane (PU)
Cuff Type : Knitted
Colour : Hi-vis Yellow
Sizes : 7, 8, 9, 10, 11
Qty/Pack : 12 pairs
Qty/Carton : 120 pairs



PRODUCT CODE: AFYPU(SIZE)



PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	12.5cm +/-	22.5cm +/-
8	12.8cm +/-	23.0cm +/-
9	13.0cm +/-	25.5cm +/-
10	13.8cm +/-	26.0cm +/-
11	14.5cm +/-	28.5cm +/-

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

STANDARDS

CE CATEGORY:

II Intermediary risk in accordance with:
 EN 420 / AS / NZS2161.2:2005 General Requirements
 EN 388:2016 Protection Against Mechanical Risks
Results - 4X43D
 ASTM F1790 Cut Level
Results - 4

www.prosafetygear.com

PERTH
 T [618] 9301 7888
 F [618] 9301 7889

MELBOURNE
 T [613] 9764 9900
 F [613] 9764 9800

SYDNEY
 T [612] 9601 3877
 F [612] 9601 3899

BRISBANE
 T [617] 3806 2699
 F [617] 3806 3266

ADELAIDE
 T [613] 9762 2500
 F [613] 9762 3500
 M 0424 504 802

NEW ZEALAND
 T [649] 525 8090
 F [649] 523 9773

E wa@paramountsafety.com.au

E vic@paramountsafety.com.au

E nsw@paramountsafety.com.au

E qld@paramountsafety.com.au

E sa@paramountsafety.com.au

E nz@paramountsafety.co.nz