

PROSENSE C5 CUT RESISTANT PU DIPPED GLOVE

PRODUCT CODE: C5PUD(SIZE)

FEATURES & BENEFITS

- EN388:2016 Cut Resistance Level "D".
- Good cut resistance without sacrificing comfort or dexterity.
- Polyurethane finish coated palm.
- Breathable liner.
- Form fitting for comfortable all day wear.
- Colour coded cuff for size identification.
- Anti-static.

APPLICATIONS

Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut & Abrasion Risks

PRODUCT DETAILS

Material : Engineered Composite 15 Gauge Seamless Liner

Dip : Polyurethane (PU)

Cuff Type : Knitted

Colour : Grey Speckled Liner, Black PU Palm

Sizes : 7, 8, 9, 10, 11, 12

Qty/Pack : 12 pairs

Qty/Carton : 120 pairs

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	9.5cm +/- 0.3	23.5cm +/- 0.5
8	9.8cm +/- 0.3	24.5cm +/- 0.5
9	10.2cm +/- 0.3	25.5cm +/- 0.5
10	10.6cm +/- 0.3	26.0cm +/- 0.5
11	11.0cm +/- 0.3	27.0cm +/- 0.5
12	11.2cm +/- 0.3	28.0cm +/- 0.5

STANDARDS

CE CATEGORY:

II Intermediary risk in accordance with:
 EN 420 / AS / NZS2161.2:2005 General Requirements
 EN 388:2016 Protection Against Mechanical Risks

Results - 4X43D




PRODUCT CODE: C5PUD(SIZE)



AS/NZS2161.3
ID No
BMP 668611



4X43D

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

www.prosafetygear.com

PERTH

T [618] 9301 7888
F [618] 9301 7889

E wa@paramountsafety.com.au

MELBOURNE

T [613] 9764 9900
F [613] 9764 9800

E vic@paramountsafety.com.au

SYDNEY

T [612] 9601 3877
F [612] 9601 3899

E nsw@paramountsafety.com.au

BRISBANE

T [617] 3806 2699
F [617] 3806 3266

E qld@paramountsafety.com.au

ADELAIDE

T [613] 9762 2500
F [613] 9762 3500
M 0424 504 802

E sa@paramountsafety.com.au

NEW ZEALAND

T [649] 525 8090
F [649] 523 9773

E nz@paramountsafety.co.nz